





# Residential Window and Exterior Door Specification

In case of conflict, the Home Plus Program Rider's Terms and Conditions prevail.

### Qualified Installer must:

- Be licensed and insured in Massachusetts to perform work being contracted. Must provide license number and proof of insurance.
- Provide references available upon request.
- Provide full Scope of Work and detailed quote.
- Assist customer with rebate submission through WG+E Ways to Save online application.

Windows and Exterior Doors must be Energy Star NFRC Rated to meet the following specifications:

Upgrade Type	Glazing Level	U-Factor	SHGC
Window	n/a	≤0.22	≥0.17
Exterior Door	Opaque	≤0.17	No Rating
Exterior Door	≤½ Lite	≤0.23	≤0.23
Exterior Door	≥½ Lite	≤0.26	≤0.40

#### **Definitions**

#### Window

An assembled unit consisting of a frame/sash component holding one or more pieces of glazing functioning to admit light and/or air into an enclosure and designed for a vertical installation in an external wall of a Residential Building. Includes Transoms.

#### **U-Factor**

The heat transfer per time per area and per degree of temperature difference (Btu/h ft2 $\,^{\circ}$ F). The U-Factor multiplied by the interior-exterior temperature difference and by the projected fenestration product area yields the total heat transfer through the fenestration product due to conduction, convection, and long-wave infra-red radiation.

#### **Solar Heat Gain Coefficient (SHGC)**

The ratio of the solar heat gain entering the space through the fenestration product to the incident solar radiation

#### **Exterior Door**

A sliding or swinging entry system designed for and installed in a vertical wall separating conditioned and unconditioned space in a Residential Building. Includes Sidelites.

- i) Opaque Glazing: A Door or Sidelite with no glazing (per NFRC 100).
- ii)  $\leq \frac{1}{2}$ -Lite Glazing: A Door with  $\leq 900$  in 2 (0.581 m2) of glazing or a Sidelite  $\leq 281$  in 2 (0.181 m2) of glazing (per NFRC 100). Includes  $\frac{1}{2}$  and  $\frac{1}{2}$ -lite Doors and Sidelites.
- iii) > ½-Lite Glazing: A Door with > 900 in 2 (0.581 m2) of glazing or a Sidelite with > 281 in 2 (0.181 m2) of glazing (per NFRC 100). Includes ¾-lite and fully glazed Doors and Sidelites







## Customer may use Sample Bid Language provided below to collect bids from three contractors.

tor.	
ame), located at	(customer
(contracto	name) for the following services:
	nme), located at

The scope of work shall include the following:

- Contractor must be licensed and insured in Massachusetts to perform work being contracted. Must provide proof of license and insurance.
- Proposal describing unit(s), installation, clean up and removal, fee schedule, and any unique circumstances.
- Note: site must be left in same or improved condition. All trash, packaging, and other materials must be removed by the contractor.
- All required City of Westfield permits must be obtained and paid by contractor.
- Contractor must assist customer with rebate submission through WG+E Ways to Save online application.
- Unit(s) must meet the specifications below:

Upgrade Type	Glazing Level	U-Factor	SHGC
Window	n/a	≤0.22	≥0.17
Exterior Door	Opaque	≤0.17	No Rating
Exterior Door	≤½ Lite	≤0.23	≤0.23
Exterior Door	≥½ Lite	≤0.26	≤0.40